

Specifications

Basic

Model	RG-ES205GC-P	RG-ES205GC	RG-ES206GC-P	RG-ES208GC	RG-ES209GC-P
10/100/1000Base-T ports	5	5	6	8	9
1000Base-X SFP ports	-	-	-	-	-
PoE/PoE+ ports	4	-	4	-	8
Max. PoE budget	54W	-	54W	-	120W
Layer Type	Layer 2	Layer 2	Layer 2	Layer 2	Layer 2
Switching capacity	10 Gbps	10 Gbps	12 Gbps	16 Gbps	18 Gbps
Forwarding rate	7.44 Mpps	7.44 Mpps	8.93 Mpps	11.90 Mpps	13.39 Mpps
Packet Buffer	1 Mbit	1 Mbit	1 Mbit	1.5 Mbit	1.5 Mbit
MAC address table	2000	2000	4000	4000	4000
Maximum VLAN Support	16	16	16	16	16
Dimensions (W x D x H)	148 mm x 78 mm x 26 mm	119 mm x 75 mm x 24 mm	148 mm x 78 mm x 26 mm	160 mm x 75 mm x 24 mm	202 mm x 108 mm x 28 mm
Weight (With package)	0.9 kg	0.36 kg	0.79 kg	0.49 kg	1.3 kg
MTBF	> 200,000	> 200,000	> 200,000	> 200,000	> 200,000
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years

Software Features

10/100/1000M Auto/Full/Half Duplex Negotiation	✓	✓	✓	✓	✓
Flow Control	✓	✓	✓	✓	✓
Storm Suppression	✓	✓	✓	✓	✓
Management IP	10.44.77.200	10.44.77.200	10.44.77.200	10.44.77.200	10.44.77.200
VLAN Range	1 - 4094	1 - 4094	1 - 4094	1 - 4094	1 - 4094
Port-based VLAN	✓	✓	✓	✓	✓